

# PIM-150-C

## User Manual







This product uses vivid color, high-definition display screen, and smooth operation touch screen, with wireless design.

This manual offers technical information about the product.

## **Specification**

<b>Backlight</b>	Led
<b>Brightness</b>	300 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	1500:1
<b>Viewing Angle</b>	Horizontal:170°/ Vertical: 170°
<b>Response Time</b>	35ms(GTG)
<b>Display Color</b>	16.2M Colors
<b>Display Resolution</b>	1024 x 768 (4:3)
<b>Refresh Frequency</b>	60Hz
<b>Input Resolution</b>	1024 x768 @ 60Hz
<b>Connector</b>	VGA / DVI / HDMI
• OSD	
<b>OSD Control</b>	Button
<b>OSD Language</b>	English, Chinese
• Touch Screen Parameters	
<b>Glass</b>	3mm Tempered Glass with Black Silk-screen
<b>Touch Point</b>	10
<b>Touch Technology</b>	Projecting Capacitance (G+G)
<b>Type of Pen</b>	Fingers, Hands with Gloves, Conductive Stylus
<b>Waterproof</b>	Touch surfaces will not be affected by water droplets or steam
<b>Calibration</b>	No Calibration Tool
<b>Response Time</b>	7ms-12ms
<b>Connect</b>	USB2.0(Type-B)
<b>Multi Touch Protocol Support</b>	Windows
<b>Operating System</b>	Win 7/8,Android,Linux
• Mechanical Parameters	
<b>Size</b>	352 x 276 x 47 mm
<b>Packaging Size</b>	440 x 325 x 90 mm
<b>Weight(about)</b>	3.5kg/4.5kg
<b>Hanging Method</b>	VESA,MIS-D,100,C
• Electrical Parameters	
<b>Power Input</b>	DC in: DC 12V3A (50/60 Hz)
<b>Power Supply</b>	≤ 14W (typ.)
<b>Standby Power</b>	≤ 2W (typ.)



